


P1 — WIRING TABLE — P2

GROUND	A1	-----	B1	GROUND
RX0+	A2	←	B2	TX0+
RX0-	A3	←	B3	TX0-
GROUND	A4	-----	B4	GROUND
RX1+	A5	←	B5	TX1+
RX1-	A6	←	B6	TX1-
GROUND	A7	-----	B7,B12	GROUND
RX2+	A8	←	B13	TX2+
RX2-	A9	←	B14	TX2-
GROUND	A10	-----	B15	GROUND
RX3+	A11	←	B16	TX3+
RX3-	A12	←	B17	TX3-
GROUND	A13	-----	B18	GROUND
GROUND	B13	-----	A18	GROUND
Tx3-	B12	○	A17	RX3-
TX3+	B11	○	A16	RX3+
GROUND	B10	-----	A15	GROUND
TX2-	B9	○	A14	RX2-
TX2+	B8	○	A13	RX2+
GROUND	B7	-----	A7,A12	GROUND
TX1-	B6	○	A6	RX1-
TX1+	B5	○	A5	RX1+
GROUND	B4	-----	A4	GROUND
TX0-	B3	○	A3	RX0-
TX0+	B2	○	A2	RX0+
GROUND	B1	-----	A1	GROUND

5	SR	1
4	36PIN CABLE END CONNECTOR w/OVERMOLD	1
3	26PIN UNIVERSAL KEY (2,4,6) COVER KIT W/BLUE LATCH	1
2	26PIN CABLE END CONNECTOR	1
1	INTERNAL SAS CABLE (30AWG x 8PAIR),100ohm, UL APPROVED	A/R
ITEM	DESCRIPTION	Q'TY



高位企業有限公司 Yes Way Enterprise Corp.		TOLERANCE UNSPECIFIED	
SCALE X UNIT mm		.000 ± .00 ± .0 ± ±	
NAME MINI SAS 36P-MINI SAS 26P CABLE ASS'Y		SHEET 1 / 1	DRAWN 7/6/2007 Vivian
DRAWING NO. 5C36A12-X100		REV A0	DESIGNER Reo
		CHECKED Jenny	APPROVED Tim

RoHS product

A3