



TWIST CABLE SPAN=125mm
TOLERANCE ± 15mm

PIN ASSIGNMENT :

Conn A :	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
Conn B :	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
Conn A :	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
Conn B :	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
Conn A :	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54
Conn B :	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54
Conn A :	55	56	57	58	59	60	61	62	63	64	65	66	67	68				
Conn B :	55	56	57	58	59	60	61	62	63	64	65	66	67	68				

REV.	ZONE	LTR	DESCRIPTION	DATE	REVISER	APPD
------	------	-----	-------------	------	---------	------

	1	LVD TERM.	3	S68D33-VS
	750mm	.635mm 68P,TP 30AWG	2	CFC68-E-075
Black	5	HPD-68M 0.635mm,DC	1	SIA68M-13P-C1
REMARK	Q'TY	PART NAME	NO.	PART NO.
高位企業有限公司 Yes Way Enterprise Corp.			TOLERANCE UNSPECIFIED	
SCALE		UNIT	.000	±
1 : 1		mm	.00	±
NAME		SHEET	.0	±
ULTRA 2 SCSI		1	.0	±
FLAT CABLE A'SSY		1	ANGLE	±
DRAWING NO.		REV	DRAWN	Vivian 1/8/2002
P68M56-X075		0	DESIGNER	Reo
14-000102680		A3	CHECKED	Jenny
			APPROVED	Tim