



NOTE :
 1. Other pins are passthrough.
 2. Resistor tolerance is $\pm 2\%$.
 3. P cable single-end 9 lines active terminator.

PACKING LIST		1 PIECE IN A PLASTIC BAG CARTON MEAST: 33cm * 25cm * 41cm		
PART NUMBER	TYPE	QUANTITY	NET WEIGHT	GROSS WEIGHT
S68A26-A	ACTIVE	100	10 KGS.	11 KGS.

PIN ASSIGNMENT :

Conn A : 35 36 37 38 39 40 41 42 43 44 45 46 47 48 55 57 58 59

Conn B : 2 4 6 8 10 12 14 16 18 32 36 38 40

Conn A : 60 61 62 63 64 65 66 67 68

Conn B : 42 44 46 48 50

1.BELOW ARE OPEN

Conn A : 19,53

Conn B : 25

2.BELOW ARE TERM PWR

Conn A : 17,18,51,52

Conn B : 26

3.OTHER PIN IS GROUND

	1	SMD, REG, REGULATOR	8	XQT-054
	1	COVER B	5	XPL-094-DB
	1	COVER A	4	XPL-094-DA
Black G/F	1	CONVOP, 100R	8	HTZ50D-17
	1	WIPERM, 3.2mmTYPE	2	SMD88M-17P
Black	1	PCB SFL, EPD68M/DC68	1	YPL004
REMARK	Q'TY	PART NAME	NO.	PART NO.

<p>高位企業有限公司 Yes Way Enterprise Corp.</p>		TOLERANCE UNSPECIFIED	
		.000	±
<p>SCALE 1 : 1</p>		UNIT	
		mm	
NAME		SHEET	ANGLE
SCSI-3 ACTIVE TERMINATOR ASSY		1	±
		1	
DRAWING NO.		REV	CHECKED
S68A26-A		1.01	Ruby
			APPROVED
			Chris
		A3	